

# Glydea 35e and 60e RTS Programming Instructions

## DESCRIPTION

### 2 motors: Glydea 35e RTS, Glydea 60e RTS

- AC 120 V with integrated power supply – 10 foot cable
- Motor placement left or right and/or upside down installation
- New touch motion
- Comes in Dry contact with optional RTS plug-in module



## BEFORE YOU BEGIN

Manually move drapery to a middle position along the track. This allows for movement of the motor in either direction.

## Connect Power To Motor

Motors are equipped with a Nema power plug.

## Programming the RTS control point

**STEP 1:** Press and hold the OPEN/UP ▲ and CLOSE/DOWN ▼ buttons simultaneously on the RTS transmitter until the drapery jogs.

**STEP 2:** Briefly press OPEN/UP ▲ or CLOSE/DOWN ▼, the drapery automatically runs to record both hard stop positions.

## Checking the direction of operation

**STEP 1:** Press the RTS transmitter OPEN/UP ▲ button.

–If the drapery opens, the direction of rotation of correct.

–If the drapery closes, the direction of rotation is incorrect: move to the next step.

**STEP 2:** Press the my (STOP) button until the drapery jogs: the direction of rotation has been modified.

**STEP 3:** Press the OPEN/UP ▲ button to check the direction of rotation.



### Recording the RTS Transmitter:

Press the PROGRAMMING BUTTON on the back of the RTS transmitter until the motor jogs. The RTS transmitter is permanently recorded.

## Setting Intermediate Preferred “My” Position

### Recording “MY” favorite position:

To set the my (STOP) position, move the drapery to the desired intermediate position with the OPEN/UP ▲ or CLOSE/DOWN ▼ buttons then press the my (STOP) button until the drapery jogs.

### Delete the “MY” position:

To delete the my (STOP) position, move to the current my (STOP) position, then press the (STOP) button until the drapery jogs.

## Adjusting The Limits

### OPEN/UP Limit Adjustment:

**STEP 1:** Press the OPEN/UP ▲ button, to move the drapery to the limit to be re-adjusted.

**STEP 2:** Press and hold the OPEN/UP ▲ and CLOSE/DOWN ▼ buttons simultaneously until the drapery jogs.

**STEP 3:** Press and hold the OPEN/UP ▲ or CLOSE/DOWN ▼ buttons to move the drapery to the new desired position.

**STEP 4:** To confirm the new limit, press and hold the my (STOP) button until the drapery jogs.

## Adjusting The Limits

### CLOSE/DOWN Limit Adjustment:

**STEP 1:** Press the CLOSE/DOWN ▼ button to move the drapery to the limit to be re-adjusted.

**STEP 2:** Press and hold the OPEN/UP ▲ and CLOSE/DOWN ▼ buttons simultaneously until the drapery jogs.

**STEP 3:** Press and hold the OPEN/UP ▲ or CLOSE/DOWN ▼ buttons to move the drapery to the new desired position.

**STEP 4:** To confirm the new limit, press and hold the my (STOP) button until the drapery jogs.

## Modifying the motor Rotation Direction

**STEP 1:** Press OPEN/UP ▲ or CLOSE/DOWN ▼ to move the drapery away from the limit:

**STEP 2:** Press and hold the OPEN/UP ▲ and CLOSE/DOWN ▼ buttons simultaneously until the drapery jogs.

**STEP 3:** Press the my (STOP) button until the drapery jogs to reverse the rotation direction.

## Dry Contact Mode Setting

**STEP 1:** Press OPEN/UP ▲ or CLOSE/DOWN ▼ to move the drapery away from the limit:

**STEP 2:** Press and hold the OPEN/UP ▲ and CLOSE/DOWN ▼ buttons simultaneously until the drapery jogs.

**STEP 3:** Press the my (STOP) and CLOSE/DOWN ▼ buttons simultaneously until the drapery jogs to change the ergonomoy.

## Activating the Touch Motion Feature

**NOTE: The Glydea by default does not have the touch motion feature activated.**

**STEP 1:** Press OPEN/UP ▲ or CLOSE/DOWN ▼ to move the drapery away from the limit.

**STEP 2:** Press and hold the OPEN/UP ▲ and CLOSE/DOWN ▼ button simultaneously until the draperies jogs.

**STEP 3: NOTE – Be sure to only follow the steps associated with your desired sensitivity setting.**

### To Activate the Standard Sensitivity Setting

Press the OPEN/UP ▲ and CLOSE/DOWN ▼ buttons simultaneously until the drapery jogs (total of two jogs) then proceed to Step 4.

### To Activate the Low Sensitivity Setting

Press the OPEN/UP ▲ and CLOSE/DOWN ▼ buttons simultaneously until the drapery jogs once. Then Press the OPEN/UP ▲ and CLOSE/DOWN ▼ buttons simultaneously until the drapery jogs again (total of three jogs). Proceed to Step 4.

**STEP 4:** Press the my (STOP) button until the drapery jogs to confirm the setting.

## Adjustment Of Speed Setting

**STEP 1:** Press and hold both the my (STOP) and OPEN/UP ▲ buttons simultaneously until the drapery starts to open and close automatically without stopping.

**STEP 2:** Press OPEN/UP ▲ to increase speed, CLOSE/DOWN ▼ to decrease speed

**STEP 3:** Press the my (STOP) button until the drapery jogs to confirm the setting.

## Adding/Deleting RTS



**STEP 1:** Press and hold the PROGRAMMING BUTTON of either the motors receiver or a transmitter already in memory until the drapery jogs. The motor is now in **PROGRAMMING MODE**.

**STEP 2:** Briefly press the PROGRAMMING BUTTON of the transmitter to add or delete, until the drapery jogs.

## Deleting Previous Setting

To delete all the transmitters programmed and retain limit setting, press and hold the receivers PROGRAM BUTTON until the drapery jogs twice.

**Resetting completely the memory of the motor,** press the receiver PROGRAM BUTTON until the drapery jogs 3 times. All the settings are erased.

